

Galaxy 10 Series

Standard features

- Full 21' Safety Plate Platform
- Nylon slide pads on all 3 sides of sub frame
- Front and rear tie down slots
- Positive bed lock down system
- Landing legs
- Solid side rails
- Side mount 8,000 lb. Hydraulic winch with two 4 Ton snatch blocks
- Winch clutch release winch cable tensioner
- Back up lights
- FMVSS 108 lighting
- Independent wheel lift with pivoting "L" arms
- Safety chains
- Mud flaps
- Hydraulic pump
- Full height steel headboard
- Pre-Assembled and Factory tested

Optional Equipment

- PTO
- Switch panel
- Light bar
- Work lights (upper/lower)
- Various chain and strap assemblies
- Installation

Note

Specifications subject to change without notice. All ratings are based on the structural factors only, not vehicle capacities or capabilities.

Distributed by:



Bed Specifications

Platform Length	21'
Load Rating	*10,000 lbs.
Platform Thickness	3/19" Steel
Steel Crossmembers	2 3/5" x 2 4/5" on 8" Centers
Overall Width	102"
Inside Width	98.8"
Controls	5 Spool Mono-Block Valve
Winch Rating (1st layer)	8,000 lb.
Cable Diameter and Length	3/8" x 50'

**Platform rating is based on equally distributed load.*

Wheel-lift Specifications

Lift Rating at Full Extension	6,000 lbs.
Tow Rating at Full Extension	6,000 lbs.

Truck Recommendations

Minimum GVW	25,000
Maximum GVW	28,000
Recommended Tire Size	19.5"
Minimum Height from Ground to top of Frame	40"
Maximum Height from Ground to top of Frame	44"
Recommended Cab to Axle (C.A.)	21' - 144"



Hadley Towing Equipment

11819 Hadley St. Whittier, CA 90601
(888) 659-8899 or (562) 695-8899

Ratings are based on structural factors only, not chassis capacity. Galaxy reserves the right without notice and without obligation, to improve or modify products, which may change the specifications, models and features availability.