

Galaxy 4000

Standard features

- Pivoting L-arm system
- Safety chains
- Variable speed hydraulic winch
- 3/8" by 100' wire rope
- Single recovery anchor
- Hydraulic pump
- Federal standard # 108 lighting
- Pre-assembled and tested
- Lubrication fittings on all shafts and other moving parts
- Winch clutch release

Optional Equipment

- PTO
- Towing sling
- Switch panel
- Mud flaps
- Fold down light bar brackets
- Convenience groups
- Trailer Ball attachment
- One-piece anchor spade
- Inside controls
- Emergency lighting
- Cable tensioners
- Light pylon
- Work area lighting
- 24" or 48" tunnel tool compartment

Recovery Boom

Retracted	16,000 lbs.
Extended at 34° (TEMA)	4,000 lbs.
Maximum Lift Angle	39°
Maximum Hook Height	13'
Reach Past Underlift Lowered	76 1/2"

Winch

Worm Gear	8,000 lbs.
-----------	------------

Cable

Per Winch	3/8" x 100'
-----------	-------------

Cab to Axle

Minimum Cab to Axle - Standard Body (Clear)	60"
Maximum Cab to Axle - w/Spacer Boxes (Clear)	84"

Suggested Chassis

GVWR	15,000 lbs.
------	-------------

Underlift

Lift Capacity Extended with Forks	4,500 lbs.
Lift Capacity Extended on Wheel Lift	4,000 lbs.
Tilt Capacity Fully Extended 2/Forks	4,500 lbs.
Maximum Reach to Center of Forks	65"
Tow Rating	10,000 lbs.



Distributed by:



Galaxy

Hadley Towing Equipment

11819 Hadley St. Whittier, CA 90601
(888) 659-8899 or (562) 695-8899

Ratings are based on structural factors only, not chassis capacity. Galaxy reserves the right without notice and without obligation, to improve or modify products, which may change the specifications, models and features availability.