

# Galaxy Self Loader

## Standard features

- Self Loading Integrated boom with Hydraulic Crossbar
- Safety chains
- Wheel Straps
- 8,000 lb Variable speed hydraulic winch
- 3/8" by 100' wire rope
- Two recovery anchors
- Hydraulic pump
- Federal standard # 108 lighting
- Pre-assembled and tested
- Lubrication fittings on all shafts and other moving parts
- Winch clutch release
- Wired remote

## Optional Equipment

- PTO
- Towing sling
- Switch panel
- Mud flaps
- Fold down light bar brackets
- Convenience groups
- Trailer Ball attachment
- One-piece anchor spade
- Emergency lighting
- Cable tensioners
- Light pylon
- Work area lighting
- 24" Tunnel tool compartment
- 48" Tunnel tool compartment

Distributed by:



## Bed Specifications

At Boom Swivel	16,000 lbs.	
Maximum Boom Elevation	20°	
Lift Height at Maximum Elevation		
Retracted	75"	
Extended	93"	
Reach Past Tailgate	Minimum Elevation	52"
(Both extended)	Maximum Elevation	38 1/2"
Boom Rating at Boom Swivel		
Retracted	16,000 lbs.	
Extended	4,000 lbs.	

## Wheel-lift Specifications

Retracted Distance from Tailgate at Normal Tow Position	53"
Extended Distance from Tailgate at Normal Tow Position	76"
Maximum Hydraulic Extension	23 3/5"
Lift Rating	4,000 lbs.
Tow Rating	7,500 lbs.

## Winch Rating & Cable

Rating	
(1st layer of drum) each Winch	8,000 lbs.
Diameter and Length	
(each Winch)	3/8" x 100'

## Chassis Recommendations

GVWR	15,000 - 19,000 lbs.
Minimum Cab to Axle (Clear)	60"
Maximum Cab to Axle (Clear)	84"



## Hadley Towing Equipment

11819 Hadley St. Whittier, CA 90601  
(888) 659-8899 or (562) 695-8899

Ratings are based on structural factors only, not chassis capacity. Galaxy reserves the right without notice and without obligation, to improve or modify products, which may change the specifications, models and features availability.